

REVOTIK 2GE + WIFI AC ONT

Revotik RVGPON102WAC - 2GE+WIFI ac ONU designed for fulfilling FTTH ultra-broadband access request of home and SOHO users. It supports NAT/firewall and the technology of 802.11 b/g/n/acWiFi (4T4R) so on functions. It is based on the stable and mature GPON technology, which has high performance/price ratio, and the technology of layer 3 Ethernet switch. It is high cost performance and easy to maintain, Industrial design and Powerful firewall.

SPECIAL FEATURES

- Plug and play, features auto-detecting, auto-configuration, and auto firmware upgrade, etc.
- Integrated OAM remote configuration and maintenance function.
- Support rich QinQ VLAN function and IGMP Snooping multicast feature.
- Functions like transceiver diagnostic monitoring, transmitter disable, etc.
- Fully compatibility with OLT based on Broadcom / PMC / Cortina chipset.
- Support NAT, Firewall function.
- Integrated 802.11b/g/n/ac (4T4R)

TECHNICAL PARAMETERS

Item Model No	RVGPON102WAC
PON interface	PON GSC dual-mode/single-fiber, EPON Mode
Wavelength	GPON Tx1310nm, GPON Rx 1490nm
Optical interface	SC/PC connector
LAN interface	2x10/100/1000 Mbps auto adaptive Ethernet
WAN Interface	Compliant with IEEE802.11b/g/n/ac (4T4R)
Sensitivity	<-27dBm (PX20+)
Overload	> -3dBm (PX20+)
Indicators	5 indicators, for status of power supply, PON port and 1 Giga-Ethernet port.
Power adapter input	220V AC, 50HZ
Ambient temperature	-30 ~ +70 °C
Ambient humidity	10% ~ 90% (non-condensing)
Store temperature	-30 ~ +60 °C
Store humidity	10% ~ 90% (non-condensing)



TECHNICAL PARAMETERS

Dimension (L x W x H)	80mm×80mm×25mm
Power	12V,0.5A
Power Consumption	≤4W
Weight (No Power Adapter)	About 100g
Gross weight	About 250g
Management	Support CTC OAM(EPON) Support WEB Support TELNET
Throughput	Upstream >900Mbps Downstream >960Mbps
Packet lost	14Hours /Lost 0
Security	Anti-DOS attack Prevent The Rogue DHCP Server Prevent The Rogue PPPoE Server ONU Laser always-on detection Powerful firewall function
Multicast	Support IGMPv1/v2 Support IGMP Snooping Max Multicast vlan 8 Max Multicast Group 255
VLAN	Support VLAN tag mode Support VLAN transparent mode Support VLAN trunk mode(max 16) Support VLAN 1:1 translation mode
Alarm	Support Dying Gasp Support Port Loop Detect Support Eth Port Los